

CI/SfB	(41)	R08
April 2022		

Proteus SP Data Sheet







Proteus SP Metal Spandrel Panel



Stepped Rear Spandrel Panel



Flat Spandrel Panel



What is Proteus SP?

Proteus SP is an insulated spandrel panel system that integrates into a curtain walling or window systems with an aluminium, steel, ceramic or glass facing material.

The system provides an effective way of breaking up the aesthetics of the facade or as a method of hiding floor slabs, ceilings or other building elements. Proteus SP consists of a medium-density mineral fibre core insulation that has been structurally bonded to an external face of back painted glass, porcelain ceramic or an array of aluminium & steel finishes.

The panel is inserted into a pre-prepared glazing opening before being clamped into position on all four edges within the glazing system. The configuration of your spandrel panels can be determined on a project-specific basis, by varying the metal and insulation depth to accommodate the thermal or acoustic requirements of a particular project.

Fire performance

Proteus SP is tested to achieve a classification in accordance with EN13501 for a variety of insulation depths and material finishes. See page 5 for a table of classifications. For additional materials & finishes, we will undertake project specific EN13501 classification.

Thermal Performance

The mineral fibre core insulation within the Proteus SP panel system has a linear thermal transmission of 0.038W/mK. The insulation depth can be amended to accommodate a variety of thermal performance requirements.

Acoustics

A wide variety of sound reduction values can be achieved with the Proteus SP panel by utilising different material thicknesses for the inner and outer skins of the panel. The higher the dB rating, the more mass is required within the panel. Our technical department can advise the most effective way to achieve the requirement of a project.

Large-format panels with exceptional flatness

Wide variety of material finishes and textures available

All panels are assembled at our factory and pre-finished for rapid installation on site

Composite construction can be broken down and fully recycled

Variety of insulation depths for thermal and acoustic requirements

Classified in accordance with EN13501

Manufactured to bespoke sizes

Example of a Metal Stepped Rear Spandrel Panel

1. Panel Inner Skin

Available in aluminium or steel with a wide range of finishes. Please see Materials & Finishes on page 6.

2. Adhesive

Adhesive forming a structural bond between panel insulation and skins. Adhesive applied via a CNC controlled application ensures both quality and compliance to product classification.

3. Panel Edge Insulation

High-density mineral fibre edge insulation. *Example shows minimum 20mm edge insulation thickness with a 1mm PPC aluminium outer & 0.9mm polyester aluminium inner, to match glazing thickness.

4. Panel Core Insulation

Medium-density mineral fibre core insulation. **Example shows maximum 200mm core insulation

thickness with a 1mm PPC aluminium outer & 0.9mm polyester aluminium inner, produced to suit project-specific thermal and acoustic requirements.


5. Panel Outer Skin

Available in aluminium or steel with a wide range of finishes.

Section Drawings


Curtain Wall Pressure Cap System

Flat Spandrel Panel with additional insulation to rear by Contractor




Curtain Wall Pressure Cap System

Stepped Rear Spandrel Panel




Curtain Wall Pressure Cap System

Stepped Face Spandrel Panel with additional insulation to rear by Contractor



Internally Glazed Window


Flat Spandrel Panel




Proteus SP Glass & Ceramic Spandrel Panel



Stepped Rear Spandrel Panel



Flat Spandrel Panel



Example of a Glass Flat Spandrel Panel with additional insulation to rear by Contractor


- 1. Panel Inner Skin**
Steel skin available in a range of finishes. Please see materials & Finishes on page 7.
- 2. Adhesive**
Adhesive forming a structural bond between panel insulation and skins. Adhesive applied via a CNC controlled application ensures both quality and compliance to product classification.

- 3. Panel Edge Insulation**
High-density mineral fibre edge insulation. **Example shows minimum 20mm edge insulation thickness with a 3mm porcelain ceramic outer & 0.7mm PVDF steel inner, to match glazing thickness.*
- 4. Panel Core Insulation**
Medium-density mineral fibre core insulation. ***Example shows maximum 200mm core insulation*


- thickness with a 3mm porcelain ceramic outer & 0.7mm PVDF steel inner, produced to suit project-specific thermal and acoustic requirements.*
- 5. Panel Outer Skin**
Available as back painted glass or porcelain ceramic in a range of finishes.

Section Drawings


Curtain Wall Pressure Cap System
Flat Spandrel Panel with additional insulation to rear by Contractor



Curtain Wall Pressure Cap System
Stepped Rear Spandrel Panel



Curtain Wall Pressure Cap System
Flat Spandrel Panel



Proteus SP Performance

Proteus SP Metal Spandrel Panel

Available in aluminium or steel, offering an extensive range of finishes to choose from.

The data shown here is for the thermal and acoustic performance of typical panel build-ups using mineral fibre core insulation.

Mineral fibre core insulation has a linear thermal transmission of 0.038W/mK.

Mineral fibre edge insulation has a linear thermal transmission of 0.052W/mK.

High-density mineral fibre edge insulation has a short term water absorption value of <1kg/m² and a long term value of <3kg/m².

**Other materials are available but will require project specific testing. Please contact our technical department to discuss.*

Range of Materials Available

Panel Outer Skin		Panel Inner Skin		EN13501 Classification
Material	Gauge Range	Material	Gauge Range	
PPC Aluminium	0.9mm - 5.0mm	Polyester Aluminium	0.9mm	A2-s1, d0
		Mill Finish Aluminium	0.9mm - 5.0mm	A2-s1, d0
		PPC Aluminium	0.9mm - 5.0mm	A2-s1, d0
PPC Steel	0.7mm - 3.0mm	PVDF Steel	0.7mm - 1.5mm	A2-s1, d0
		Galvanised Steel	0.7mm - 3.0mm	A2-s1, d0
		PPC Steel	0.7mm - 3.0mm	A2-s1, d0

Aluminium - Outer (mm) / Inner (mm) Thickness

Panel Thickness (mm)	1.0mm / 1.0mm		3.0mm / 1.0mm		4.0mm / 1.0mm	
	U - Value (W/m ² K)	Acoustic (dB)	U - Value (W/m ² K)	Acoustic (dB)	U - Value (W/m ² K)	Acoustic (dB)
22	1.46	27				
24	1.37	27	1.46	33		
28	1.20	27	1.28	33	1.32	35
32	1.06	27	1.13	33	1.16	35
36	0.96	27	1.01	34	1.04	36
200	0.19	39	0.19	50	0.19	53

Steel - Outer (mm) / Inner (mm) Thickness

Panel Thickness (mm)	0.7mm / 0.7mm		2.0mm / 0.7mm		3.0mm / 0.7mm	
	U - Value (W/m ² K)	Acoustic (dB)	U - Value (W/m ² K)	Acoustic (dB)	U - Value (W/m ² K)	Acoustic (dB)
22	1.46	33				
24	1.37	33	1.41	40	1.44	42
28	1.20	33	1.23	40	1.26	42
32	1.06	34	1.09	40	1.11	42
36	0.96	34	0.99	40	0.99	43
200	0.19	54	0.19	66	0.18	70

Proteus SP Glass & Ceramic Spandrel Panel

Available in back painted glass or porcelain ceramic with an extensive range of finishes offering you unique and endless contemporary design options.

The data shown here is for the thermal and acoustic performance of typical panel build-ups using mineral fibre core insulation.

Mineral fibre core insulation has a linear thermal transmission of 0.038W/mK.

Mineral fibre edge insulation has a linear thermal transmission of 0.052W/mK.

High-density mineral fibre edge insulation has a short term water absorption value of <1kg/m² and a long term value of <3kg/m².

Range of Materials Available

Panel Outer Skin		Panel Inner Skin		EN13501 Classification
Material	Gauge	Material	Gauge	
Back Painted Glass	4.0mm	PVDF Steel	0.7mm	A2-s1, d0
Porcelain Ceramic	3.0mm	PVDF Steel	0.7mm	A2-s1, d0

Glass / Ceramic - Outer (mm) / Steel - Inner (mm) Thickness

Back Painted Glass		
Panel Thickness (mm)	4.0mm / 0.7mm	
	U - Value (W/m ² K)	Acoustic (dB)
25	1.46	36
28	1.32	36
32	1.16	36
36	1.03	37
200	0.19	61

Porcelain Ceramic		
Panel Thickness (mm)	3.0mm / 0.7mm	
	U - Value (W/m ² K)	Acoustic (dB)
24	1.46	35
28	1.28	35
32	1.13	35
36	1.01	35
200	0.19	57


Materials and Finishes

Please note that all colours shown are representative in print process, we recommend that you request a swatch sample from our sales department for an accurate representation.

Pre coated and post coated aluminium

Aluminium, with its distinctive contemporary look, can be post coated in any RAL colour and can be prefinished with unique coating formulations offering long-term performance.

Material width: 1000, 1250, 1500mm
Max panel width: 970, 1220, 1470mm



Pre coated and post coated steel

Steel, with its distinctive contemporary look, can be post coated in any RAL colour and can be prefinished with unique coating formulations offering long-term performance.

Material width: 1000, 1250mm
Max panel width: 970, 1220mm



Back painted glass

Back painted glass offers a unique reflective surface. Standard ranges such as AGC Lacobel / Matelac coated to any RAL colour.


Material width: Bespoke
Max panel width: Project Specific




Porcelain Ceramic

A range of coloured porcelain ceramic materials can be provided in Marble, Stone, Cement, Wood, Metallic or Coloured.

Material size: 1000 x 3000mm
Max panel size: 990 x 2990mm



The finishes shown are a small sample of the available finishes, please see our website for more www.proteusfacades.com



Proteus Facades Limited
1 Gerrard Place, Skelmersdale
Lancashire WN8 9SU UK

Telephone +44 (0)151 545 5075
www.proteusfacades.com

© 2022 Proteus Facades Ltd

The details and information contained in this publication are correct at the point of going to press. Proteus reserves the right to change details and specifications without prior notice. No responsibility is assumed for errors or misinterpretations resulting from the information contained in this publication. All logos and trade names remain the property of their respective owners. Typical construction details are illustrative only and no liability is accepted. Latest information is available at www.proteusfacades.com